# **JENBACHER TYPE 3**

## Hot & Humid countries Efficient, durable, reliable

Long service intervals, maintenance-friendly engine design and low fuel consumption ensure maximum efficiency in our type 3 Jenbacher engines. Enhanced components prolong service life even when using non-pipeline gases, such as landfill gas. Our type 3 engines offer an outstanding service interval with up to 80,000 operating hours until the major overhaul. This engine type stands out in its 400 to 1,100 kW power range due to its technical maturity and high degree of reliability.



#### Reference installations

#### J312 & J320 Landfill Site in Durban, South Africa

Energy Source Engine type		Electrical output	Commissioning
Landfill gas	1 x J312 1 x J320	526 kW 1,064 kW	2006



At the Durban Landfill, two containerized Jenbacher generator sets with a total electrical output of 1,590 kW generate electricity for the local municipal grid. Moreover, the use of landfill gas for power generation curbs environmental pollution and health problems associated with the escaping landfill gas.

#### J316 Combined Cooling, Heat & Power Plant at the Hospital in Beijing Qinghe, China

<b>Energy Source</b>	Engine type	Electrical output	Thermal output	Commissioning
Natural gas	2 x J316	1,670 kW	1,851 kW	2012



The Qinghe Hospital building and facility installed two J316 engines with a total electrical output of 1,670 kW. With a total efficiency of more than 70%, the J316 units improve the facility's energy supply security while also providing exhaust heat and hot water.

#### **J320** Ensign Drilling Jonah Field in Wyoming, US

Energy Source Engine type		Electrical output	Commissioning	
Natural gas	24 x J320	24,168 kW	2011	



In southwest Wyoming, a major gas producer has deployed 24 J320 engines to repower a drilling rig using natural gas instead of diesel. In the Jonah field, available site gas allows the producer to capture cost savings and reduce overall site emissions.

#### **Technical data**

Configuration	V 70				
Bore (mm)	13				
Stroke (mm)	17				
Displacement / cylinder (lit)	2.4				
Speed (rpm)	1,500 (50 Hz) 1,200 / 1,800 (60 Hz)				
Mean piston speed (m/s)	8.5 (1,500 1/min 6.8 (1,200 1/min 10.2 (1,800 1/min				
Scope of supply	Generator set, cogeneration system, generator set / cogeneration in container				
Applicable gas types	Natural gas, flare gas, propane biogas, landfill gas, sewage gas special gases (e.g., coal mine gas coke gas, wood gas, pyrolysis gas				
Engine type No. of cylinders Total displacement (lit)	J312 J316 J32 12 16 2 29.2 38.9 48.				

		Dimensions I x w x h (mm)
	J312	4,700 x 1,800 x 2,300
Generator set	J316	5,200 x 1,800 x 2,300
	J320	5,700 x 1,700 x 2,300
	J312	4,700 x 2,300 x 2,300
Cogeneration system	J316	5,300 x 2,300 x 2,300
	J320	5,700 x 1,900 x 2,300
	J312	12,200 x 2,500 x 2,600
Container	J316	12,200 x 2,500 x 2,600
	J320	12,200 x 2,500 x 2,600
		Weights empty (kg)

		. ,
	J312	8,100
Generator set	J316	10,100
	J320	13,900
	J312	9,500
Cogeneration system	J316	11,200
	J320	14,400

### Outputs and efficiencies

Natural gas				1,500 1/mi	n   50 Hz		
NOx <	Туре	Pel (kW) <sup>1</sup>	Pth (kW) <sup>3</sup>	Heat rate (kJ/kWhe)²	ηel (%) <sup>2</sup>	ηth (%)	ηtot (%)
500 mg/m³ <sub>N</sub>	J320	1,067	1,258	8,964	40.2	47.5	87.7
	J320	1,000	1,200	9,000	40.0	48.1	88.1

 $<sup>^{\</sup>text{1}}$  Type 3 gas engine with site condition  $^{\varsigma}$  50m above sea level and T1  $^{\varsigma}$  40°C

All data according to full load and subject to technical development and modification.

Further engine versions available on request.





<sup>&</sup>lt;sup>2</sup> Technical data according to ISO 3046

<sup>&</sup>lt;sup>3</sup> Total heat output @ hot water 90°C-70°C